

# NEXPORT

ZERO EMISSION TRANSPORT

Category 1G

## TECHNICAL SPECIFICATIONS

### CURB WEIGHT

13,000 Kg

### GVW

18,000 Kg

### PAYLOAD

5,000 KG

### AXLE LOAD RATING

7,100 Kg + 13,000 Kg

### LENGTH

12,500 mm

### WHELLBASE

6,300 mm

### FRONT OVERHANG

2,725 mm

### REAR OVERHANG

3,475 mm

### APPROACH ANGLE

8 degrees

### DEPARTURE ANGLE

8.2 degrees

### WIDTH

2,500 mm

### EXTERIOR HEIGHT

3,400 mm

### TURNING RADIUS

11,800 mm

### GROUND CLEARANCE

250 mm

### OCCUPANT CAPACITY

45+1

### PASSENGER SEAT

McConnellMetro

### DRIVER'S SEAT

ISRI 6860

### WHEELCHAIR

POSITIONS

Two

### DOOR CONFIGURATION

2+2

### FRONT PASSENGER

DOORS

1,350 mm inward gliding

### REAR PASSENGER

DOORS

1,250 mm inward gliding

### EMERGENCY EXITS

Door, Window, Roof Hatch

### SALOON HEIGHT

> 1,850 mm

### HVAC

Thermoking \ E1200LW

### MOTOR

BYD\TZ290XSE

### MOTOR POWER

150 KW x 2

### BATTERY

BYD\6B33\*2

### BATTERY TYPE

LFP-Gen 1 blade battery

### BATTERY CAPACITY

382 KWh

### CHARGING

2 x DC CCS2

### TOP SPEED

100 KMPH

### BRAKES

Full ABS disk brake

### TYRE

295/80R22.6

### SUSPENSION

Full air ride suspension

